

Spec./Model	Unit	CMH-630 Series	CMH-800 Series	CMH-1000 Series
Travel (X/Y/Z)	mm	1,020 / 850 / 890	1,270 / 1,050 / 1,050	1,530 / 1,250 / 1,200
Table Dimension	mm	630 x 630	800 x 800	1,000 x 1,000
Table Min. Indexing Increment	Degree	1° (0.001° Opt.)	1° (0.001° Opt.)	1° (0.001° Opt.)
Spindle Type		BT-50 Gearbox Drive	BT-50 Gearbox Drive	BT-50 Gearbox Drive
Spindle Motor Output	Kw	15 / 18.5 Kw 6,000 rpm (Opt. 18 / 22 Kw 6,000 rpm) (Opt. 22 / 26 Kw 6,000 rpm)	15 / 18.5 Kw 6,000 rpm (Opt. 18 / 22 Kw 6,000 rpm) (Opt. 22 / 26 Kw 6,000 rpm)	15 / 18.5 Kw 6,000 rpm (Opt. 18 / 22 Kw 6,000 rpm) (Opt. 22 / 26 Kw 6,000 rpm)
Spindle Frame Construction		Column Traveling Construction		
Tool Magazine	mm	40 Tools (Opt. 60 / 90 / 120 Tools)		
Indexing Table Accuracy	Sec.	0.001 Degree Indexing : +/- 7.5 ; Repeatability : +/- 3 & 1 Degree Indexing : +/- 5 ; Repeatability : +/- 1.5		