

Spec./Model	Unit	DCF-14 Series	DCF-18 Series	DCF-21 Series	DCF-24 Series
Distance Between Column	mm	1,400	1,850	2,150	2,450
Table Length	mm	2,000~3,000	2,000~5,000	2,000~5,000	2,500~5,000
Table Width	mm	1,200	1,500	1,800	2,000
Travel (X/Y/Z)	M	2~3 / 1.3 / 0.8	2~5 / 1.8 / 0.8 (Opt. 1.1)	2~5 / 2.1 / 0.8 (Opt. 1.1)	2.5~5 / 2.4 / 0.8 (Opt. 1.1)
Spindle Nose To Table	mm	100 ~ 900	180 ~ 980 (120 ~ 1,220)	180 ~ 980 (120 ~ 1,220)	120 ~ 920 (120 ~ 1,220)
Spindle Motor Output		22 / 26 Kw, 6,000 rpm By Gearbox Hi-Lo Shift			
Tool Magazine	mm	24 Tools / Max. Dia. 110 or 200 (Adjacent Empty)			
Accuracy	mm	Positioning : +/- 0.015 ; Repeatability : +/- 0.003			

Spec./Model	Unit	DCF-28 Series	DCF-32 Series	DCF-36 Series	DCF-42 Series
Distance Between Column	mm	2,850	3,250	3,650	4,250
Table Length	mm	3,000~6,000	3,000~6,000	4,000~6,000	4,000~6,000
Table Width	mm	2,200	2,600	3,000	3,000
Travel (X/Y/Z)	M	3~6 / 2.8 / 1.1 (Opt. 1.4)	3~6 / 3.2 / 1.1 (Opt. 1.4)	4~6 / 3.6 / 1.1 (Opt. 1.4 / 1.5)	4~6 / 4.2 / 1.1 (Opt. 1.4 / 1.5)
Spindle Nose To Table	mm	150 ~ 1,250 (120 ~ 1,520)	150 ~ 1,250 (120 ~ 1,520)	260 ~ 1,360 (120~1,520 / 1620)	260 ~ 1,360 (120~1,520 / 1620)
Spindle Motor Output		22 / 26 Kw, 6,000 rpm (Opt. 30 / 37 Kw, 4,500 rpm) By Gearbox Hi-Lo Shift			
Tool Magazine	mm	32 Tools / Max. Dia. 125 or 220 (Adjacent Empty)			
Accuracy	mm	Positioning : +/- 0.015 ; Repeatability : +/- 0.003			