

| Spec./Model | Unit | DSW-24 Series | DSW-28 Series | DSW-32 Series |
|-------------------------|-------------|---|-----------------------|-----------------------|
| Distance Between Column | mm | 2,450 | 2,850 | 3,250 |
| Table Length | M | 6 ~ 36 (Pitch Per 1M) | 6 ~ 36 (Pitch Per 1M) | 6 ~ 36 (Pitch Per 1M) |
| Table Width | mm | 1,600 | 2,000 | 2,400 |
| Travel (X/Y/Z) | M | 6~36 / 2.4 / 1.1 | 6~36 / 2.8 / 1.1 | 6~36 / 3.2 / 1.1 |
| Travel (W) | M | 1.5 (Opt. 2.0) | | |
| Spindle Nose To Table | mm | 800 ~ 3,400 (720 ~ 3,820 Subject To Design) | | |
| Spindle Motor Output | | 22 / 26 Kw , 6,000 rpm (Opt. 30 / 37 Kw, 4,500 rpm) By Gearbox Hi-Lo Shift | | |
| Tool Magazine | mm | 32 Tools / Max. Dia. 125 or 220 (Adjacent Empty) | | |
| Accuracy | mm | Positioning : +/- 0.015 ; Repeatability : +/- 0.003 | | |

| Spec./Model | Unit | DSW-36 Series | DSW-42 Series | DSW-48 Series | DSW-54 Series |
|-------------------------|-------------|--|-----------------------------------|-----------------------------------|-----------------------------------|
| Distance Between Column | mm | 3,650 | 4,250 | 4,850 | 5,450 |
| Table Length | M | 6 ~ 36 (Pitch Per 1M) | 6 ~ 36 (Pitch Per 1M) | 6 ~ 36 (Pitch Per 1M) | 6 ~ 36 (Pitch Per 1M) |
| Table Width | mm | 2,800 | 3,400 | 4,000 | 4,600 |
| Travel (X/Y/Z) | M | 6~36 / 3.6 / 1.1 (Opt. 1.4 / 1.5) | 6~36 / 4.2 / 1.1 (Opt. 1.4 / 1.5) | 6~36 / 4.2 / 1.1 (Opt. 1.4 / 1.5) | 6~36 / 4.2 / 1.1 (Opt. 1.4 / 1.5) |
| Travel (W) | M | 1.5 (Opt. 2.0) | | | |
| Spindle Nose To Table | mm | 800 ~ 3,400 (720 ~ 4,220 Subject To Design) | | | |
| Spindle Motor Output | | 22 / 26 Kw, 6,000 rpm (Opt. 30 / 37 Kw, 4,500 rpm) By Gearbox Hi-Lo Shift | | | |
| Tool Magazine | mm | 32 Tools / Max. Dia. 125 or 220 (Adjacent Empty) | | | |
| Accuracy | mm | Positioning : +/- 0.015 ; Repeatability : +/- 0.003 | | | |